

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 October 2005 (27.10.2005)

PCT

(10) International Publication Number
WO 2005/101599 A1

(51) International Patent Classification⁷:
5/026, 5/04, 5/343, 5/40

H01S 5/183,

(74) Agent: ITOH, Tadahiko; 32nd Floor, Yebisu Garden
Place Tower, 20-3, Ebisu 4-chome, Shibuya-ku, Tokyo
150-6032 (JP).

(21) International Application Number:

PCT/JP2005/007269

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(22) International Filing Date: 7 April 2005 (07.04.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-118755 14 April 2004 (14.04.2004) JP

(71) Applicant (for all designated States except US): RICOH
COMPANY, LTD. [JP/JP]; 3-6, Nakamagome 1-chome,
Ohta-ku, Tokyo, 1438555 (JP).


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): TAKAHASHI,
Takashi [JP/JP]; 24-7-103, Yamadauenodaicho, Tai-
haku-ku, Sendai-shi, Miyagi, 9820815 (JP).

[Continued on next page]

(54) Title: VERTICAL CAVITY SURFACE EMITTING SEMICONDUCTOR LASER, LIGHT EMISSION DEVICE, AND OP-
TICAL TRANSMISSION SYSTEM



(57) Abstract: A semiconductor laser is disclosed with which a VCSEL can be constituted with a simplified configuration for optical transmission at a transmission rate higher than 10 Gbps. The semiconductor laser includes a resonator including a first active region able to emit light in response to current injection and a second active region able to emit light in response to external excitation light. Multilayer film reflecting mirrors sandwich the resonator from two opposite sides. The first active region and the second active region generate light at a wavelength the same as the resonance mode of the resonator.

WO 2005/101599 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.